



EXISTING SURVEYS

Original Government Survey				Original Survey Evidence Found			
Year Surveyed:		By:		Date of Search:		By:	
Original Monument:				Monument Found:			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Subsequent Corner Restoration				Evidence of Subsequent Corner Restoration Found			
Where Filed or Recorded: Book: S.Bk.2 Page: 183 Date: 1871 Monument Set: Not Indicated				Year Searched: Monument Found			
Species	Diameter	Bearing	Distance	Species	Diameter	Bearing	Distance
Sugar	12"	S 3°E	17 Lks				
W.Oak	4"	S61°E	21 Lks				

OTHER EVIDENCE

Describe corner loc. relative to nearby features & dir. to corner location; note fences, roads, etc.	Sketch of Monument
The monument is located on a north facing slope, 29' east of fence running south and west, the stone is leaning slightly down the hill to the north.	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.			
Center East 1/16; A 0.3'x0.5' sandstone was found 0.5' above grade with a chiseled "+" on top. This corner was established on a 1891 Legal Survey found in Survey Book 2, page 183-184 by Alexander Spencer.			
Corner Diagram	Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.		
	3-1/3" Maple N50°W 6.0' 3-1/2" Dogwood S55°E 30.2' 13" Beech (Fence Corner) N85°W 28.5'		
	Corner Recordation:		Certificate Prepared:
	Filed and Recorded in County records:		Date:
	Book:		Page:
Section: 20	Geodetic Coordinates:	Lat./N.	Long./E.
	Edited By:	BTR	Date Created: 10/2004

Referenced on BRG survey recorded as InstNo.2005011737.

Accepted by the Monroe County Surveyor Review Board on August 6, 2019.